

## Erdbohrer ( MTAG )



Technische Daten	Bohrer-gewicht (kg)	Bagger-gewicht (t)	Drehmoment (Nm)	Betriebsdruck (bar)	Ölbedarf (l / min.)	Antriebs-vierkant (mm)	Drehzahl (U./min.)	Bohr-schnecke	Verlängerung Optional (m)
MTAG-03	90	0,75 – 2	1700	240	15-45	57	30-90	MA 20-MA 60	1 – 1,5
MTAG-05	98	2 – 5	3250	240	25-60	57	35-85	MA 20-MA 60	1 – 1,5
MTAG-08	107	5 – 8	5600	240	25-75	57	18-55	MA 20-MA 90	1 – 1,5
MTAG-13	155	8 – 25	12100	240	90-180	75	35-70	MA 20-MA 120	1,5
MTAG-18	162	20 – 32	17700	240	90-220	75	20-52	MA 20-MA 150	1,5
MTAG-25	312	20 – 40	32500	240	90-220	100	12-26	MA 30-MA 150	1,5

Bohrschnecke	Durchmesser (mm)	Länge (mm)
MA 20	200	900
MA 25	250	900
MA 30	300	900
MA 35	350	1200
MA 40	400	1200
MA 45	450	1200
MA 50	500	1200
MA 60	600	1200
MA 75	750	1200
MA 80	800	1200
MA 90	900	1600
MA 100	1000	1600
MA 120	1200	1600
MA 130	1300	1600